

AG-HS001

American Power Pump Hospital Transport
Hydraulic Stretcher



Global B2B Marketplace Focused On The Supply And Procurement Of
Medical Equipment And Devices

Functions



AG-HS001

- Five-Function Luxurious Hydraulic Stretcher Is The Top Class Emergency Equipment Which Is Special For Patients' Transfer.
- It Uses The Cold-Roll Steel Sheets, Electrophoretic Coating And Powder Coating Processing.
- Equipped With American Hydraulic Pump System, Two Pumps Are More Convenient For Maintenance And Operation.

Working Environment



- Ambient Temperature: 5 °C ~ 40 °C
- Relative Humidity: Less Than 85%
- Atmospheric Pressure: 860hpa ~ 1060hp
- Transport And Storage:
- Ambient Temperature: -40 °C ~ 55 °C
- Relative Humidity: ≤ 95%

Notes For Use



- Each Part Of The Stretcher Should Keep Clean, Acidic And Alkaline Cleaning
- Time To Do The Maintenance For Hydraulic System.
- Should Be Repaired By Professional Person, Requires The Company To Provide Services, Please Contact The Distributor Or The Our After-Sales Service In Time.

After-Sale Service



- The Product Warranty Period For 18 Months From The Date Of Purchase. After The Purchasing Date Will Gain Free Spare Parts And Assembling Drawing From Our Company.
- Outside The Warranty Period, The Company Responsible For Providing Accessories, Product Implements The Lifelong Service.



CPR Quick Release

One-step molding PP dust cover

Drainage hook

American bakelite plate

Dumper castors

Ajustable push handles

Back Rest X Ray Translucent

Centrally controlled brake

Technical Parameter

TECHNICAL DATA

Product Size	210×85×59/91cm
Treatment Methods	Powder Coated Steel Bed Frame
Pump	2 Hydraulic Pump,Stable And Durable
Footrest	Controlled By Hydraulic,Easy Operating
IV pole	304 stainless steel; Detachable IV pole support
Mattress	With PU Waterproof Mattress(50mm); Mattress Base:194×62cm
Wheels	Four Central-Controlled Silent Dustproof Wheels(200mm); 5th Direction Wheel

Handrails	Patent For Curve 304 Stainless Steel Implantable Handrails
Packing	2130*820*730mm/183kg
Dynamic Load Capacity	250Kg
Static Load Capacity	400Kg
Net Weight	132Kg
5 Functions	Back Section: 0-75° Leg Section: 0-30° Trendelenburg: 0-15° Anti-Trendelenburg: 0-15° Height Adjustable:59~91cm



Central control locking



Middle pedal



Handrail control



X-ray available back board



Follow Us



Jiangsu Medwish Network Technology Co., Ltd

Website: www.medwish.com
ADD: Aoyang International Building, Zhangjiagang, -
Jiangsu, 215600, China
Tel: 0086 138 1298 8917
Fax: 0086-512-58170725